


REV	CHANGE NUMBER	DESCRIPTION	DATE
1	XXXXXXX		
2	XXXXXXX		

PIN	SYMBLE
1	LED-K
2	LED-K
3	LED-A
4	LED-A
5	GND
6	XR
7	YD
8	XL
9	YU
10	GND

36	R0(D12)	11	NC
37	R1(D13)	12	NC
38	R2(D14)	13	NC
39	R3(D15)	14	RESET
40	R4(D16)	15	CS
41	R5(D17)	16	SCL
42	HSYNC	17	SDA-SDI
43	VSYNC	18	NC
44	DCLK	19	NC
45	AVDD	20	B0(D0)
46	AVDD	21	B1(D1)
47	VCC	22	B2(D2)
48	VCC	23	B3(D3)
49	DC/RS	24	B4(D4)
50	RD	25	B5(D5)
51	WR	26	NC
52	PS0	27	NC
53	PS1	28	G0(D6)
54	PS2	29	G1(D7)
55	PS3	30	G2(D8)
56	WSYNC	31	G3(D9)
57	NC	32	G4(D10)
58	OE	33	G5(D11)
59	GND	34	NC
60	GND	35	NC

NOTES:  
 1. Undefined tolerances: ±0.20  
 2. Accord with RoHS



DIMENSION	GENERAL LINEAR TOLERANCE			SELECT LEVEL
	1	2	3	
0 ~ 4	0.05	0.1	0.2	NA
4 ~ 14	0.1	0.2	0.3	
14 ~ 63	0.1	0.2	0.4	
63 ~ 250	0.2	0.4	0.6	
250 ~ 600		0.6	1.0	NA
600 ~ 4000			1.6	
LEVEL	GENERAL ANGULAR TOLERANCE			SELECT LEVEL
	1	2	3	
RANGE	1°	2°	3°	NA

MATERIAL	
DESIGNED	Richard Liang 2011/10/21
APPROVED	

UNIT	SCALE	3rd ANGLE	MODEL NAME
M/M	1:1		
PART NUMBER: RK035FQ08			
SHEET NUMBER: 1of1		REVISION:	