



REV.	DRG DATE	DESCRIPTION	DRAWN BY
1.0	12-12-02	First issue	WINDY

PIN DESCRIPTION

Pin No.	Description
1	LED1K
2	LED2K
3	I/OVCC
4	GND
5	/WR
6	DB0
7	GND
8	DB2
9	DB4
10	DB6
11	/CS
12	/RESET
13	TE
14	DB7
15	DB5
16	GND
17	DB3
18	DB1
19	DC
20	RD
21	GND
22	VDD
23	LED2A
24	LED1A

- Specification:
- 1). Viewing angle: ALL
 - 2). Display mode: 262K TFT
 - 3). Operating temp: -20°C~+70°C
 - 4). Storage temp: -30°C~+80°C
 - 5). LCD Driver IC:ILI9335
 - 6). Backlight: 4 chip White LED
 - 7). General Tolerance: ±0.2
 - 8). ROHS Request

DIMENSION	GENERAL LINEAR TOLERANCE			SELECT LEVEL
	1	2	3	
0 - 4	0.05	0.10	0.2	
4 - 14	0.1	0.15	0.3	
14 - 63	0.15	0.2	0.4	2
63 - 200	0.2	0.3	0.6	2

LEVEL	GENERAL ANGULAR TOLERANCE		
	1	2	3
RANGE	°	°	°

DRG DATE	12-12-02	TITLE	LCM OUTLINE	Rocktech Displays Limited		
CHECK	WINDY	MODEL	RK020JH100	REV.	UNIT	SIZE
CHECK		DWG No.		1.0	mm	A4
APPROVE		PAGE	1 OF 1	(3)		