


REV.	DRG DATE	DESCRIPTION	DRAWN BY
1.0			WELLING

NO.	SYMBOL
1	VDD
2	VDDI
3	RESET
4	CS
5	RS
6	WR
7	RD
8	GND
9	NC
10	NC
11	DB0
12	DB1
13	DB2
14	DB3
15	DB4
16	DB5
17	DB6
18	DB7
19	DB8
20	DB9
21	DB10
22	DB11
23	DB12
24	DB13
25	DB14
26	DB15
27	DB16
28	DB17
29	LEDA
30	LEDK1
31	LEDK2
32	LEDK3
33	LEDK4
34	GND
35	XR
36	XL
37	YU
38	YD
39	NC

- Specification:
- 1). Viewing angle: 6:00 Clock
 - 2). Display mode: 262K TFT/Transmissive
 - 3). Operating temp: -20°C~+70°C
 - 4). Storage temp: -30°C~+80°C
 - 5). LCD Driver IC:ILI9341v
 - 6). Backlight: 4 chip White LED
 - 7). General Tolerance: ±0.2
 - 8). ROHS Request

注：弯折出货

LED Source(CIRCUIT DIAGRAM)



DIMENSION	LEVEL			SELECT LEVEL
	1	2	3	
0 ~ 4	0.05	0.15	0.2	1
6 ~ 14	0.1	0.15	0.2	2
16 ~ 85	0.15	0.2	0.3	2
85 ~ 250	0.2	0.4	0.5	2

LEVEL	GENERAL ANGULAR TOLERANCE		
	1	2	3
RANGE	<	2'	2

DRG DATE	15.11.19	TITLE	LCM OUTLINE	Rocktech Displays Limited		
CHECK	WELLING	MODEL	RK028HI003	REV.	UNIT	SIZE
CHECK		DWG No.		1.0	mm	A4
APPROVE		PAGE	1 OF 1			(3)